

THE GOVERNMENT OF ROMANIA

DECISION no 1135/2006

Regarding the minimum safety and health requirements for work on board fishing vessels

Under art.108 of the Romanian Constitution, republished,

The Government of Romania adopts the following decision:

CHAPTER I General provisions

Art.1. – (1) The present decision lays down minimum safety and health requirements applicable to work on board the vessels defined in article (2).

(2) –The provisions of the Law no. 319/2006 of safety and health at work are fully applicable to the field referred to in paragraph (1), without prejudice to more stringent and/or specific provisions contained in the Directive 89/391/EEC that is transpose in present Government Decision.

Art.2. – (1) For the purposes of the present decision, the following terms shall have the meanings hereby assigned to them:

a) “fishing vessel”: any vessel flying the Romanian flag or registered under the plenary jurisdiction of the public property or private property used for commercial purposes either for catching or catching and processing fish or other living resources from the sea;

b) “existing fishing vessel”: any fishing vessel with a length between perpendiculars of 18 meters or over and which is not a new fishing vessel;

c) “vessel”: any new or existing fishing vessel;

d) “worker”: any person carrying out an occupation on board a vessel, including trainees and apprentices but excluding shore personnel carrying out work on board a vessel at the quayside and port pilots;

e) “owner”: the registered owner of a vessel, unless that vessel has been chartered sans crew and goods or the management of vessel is assured, either wholly or in part, by a natural or legal person other than the registered owner under the terms of a management agreement; in that case, the owner who has been chartered sans crew and goods, or natural or legal person who is managing the vessel, as appropriate to be authorized owner;

f) “skipper”: the worker who, in accordance with national legislation and/or practice, commands the vessel or has responsibility for it;

(2) g) “new fishing vessel”: is any fishing vessel with a length between perpendiculars of 15 meters or over and:

a) for which the building or major conversion contract has expired on the date of coming into force of the present Government Decision or after this date;

b) the building or major conversion contract has been placed before of coming into force of the present Government Decision and which is delivered three or more years after that date; or

c) whereat, in the absence of a building contract signed on the date of coming into force of the present Government Decision or after this date, the keel was laid or the construction identifiable with a specific vessel begins, or assembly of referred to vessel has

commenced comprising at least 50 tones or 1 % of the estimated mass of all structural material, reckon with whichever is the lesser;

Art.3. – The owners shall ensure that their vessels are used without endangering the safety and health of workers, in particular in foreseeable meteorological conditions, without prejudice to the skipper's responsibility;

Art.4. - The owners shall take into account any hazards to which the workers can be exposed on board of fishing vessels, in the situations defined in Article no. 11, paragraph (2) from Law no. 319/2006.

Art.5. – (1) Any occurrences at sea which affect or could affect the safety and health of the workers on board are described in a detailed report to be forwarded to the Romanian Naval Authority and are recorded likewise, in detail in the ship's log book or, in the absence of such a log, in a corresponding document.

(2) As regards compliance of provisions orderliness with this Government Decision, Fishing Vessels are subject to regular checks by the Romanian Naval Authority and by the Labour Inspection.

(3) Certain checks concerning compliance with the provisions of this Government Decision may be carried out at sea.

CHAPTER II

New and existing fishing vessels

Art.6 - New fishing vessels must comply with the minimum safety and health requirements laid down in Annex no.1.

Art.7. - Existing fishing vessels must comply with the minimum safety and health requirements laid down in annex no.2

Art.8. - Where vessels undergo extensive repairs, conversions and alterations such extensive repairs, conversions and alterations must comply with the relevant minimum requirements laid down in Annex no. 1.

CHAPTER III

Maintenance Equipments

Art.9. - For the protection of the safety and health of workers, and without prejudice to the skipper's responsibility, the owners shall take the measures necessary to:

a) ensure that the vessels and their fittings and equipment, particularly those referred to in annexes no. 1 and 2, are technically maintained, and that any malfunctions found which are likely to affect the safety and health of workers, these may be rectified as quickly as possible;

b) take measures to ensure that the vessels and all fittings and equipment are cleaned regularly in order to maintain an appropriate standard of hygiene;

c) keep on board the vessel an adequate quantity of suitable emergency and survival equipment in good working order;

d) take account of the minimum safety and health requirements concerning life-saving and survival equipment given in annex no.3.

Art.10. - Without prejudice to the Government Decision no. 1048/2006 provisions regarding of the minimum health and safety requirements for the use by workers of

personal protective equipment at the workplace, the owner shall take account of the minimal provisions regarding of safety and health specifications of personal protective equipment, given in Annex no. 4.

Art. 11. – For the protection of the safety and health of workers, the owner place at the disposal of the skipper the means needed to enable him to fulfil the obligations imposed upon him by the present Government Decision.

CHAPTER IV **Informing, training, consulting and participation of workers**

Art.12. – (1) Without prejudice to the provisions of Article 16 and 17 of Law no. 319/2006, the workers and/or their representatives must be informed of all measures to be taken regarding safety and health on board vessels.

(2) The information referred to in paragraph (1) must be comprehensible to the workers concerned.

Art.13. – (1) Without prejudice to the provisions of Article 20 and 21 of Law no. 319/2006, workers must be given suitable training, in particular in the form of precise, comprehensible instructions, on safety and health on board vessels and on accident prevention in particular.

(2) The training referred to in paragraph (1) cover in particular fire fighting, the use of life-saving and survival equipment and, for the workers concerned, the use of fishing gear and hauling equipment as well as the use of various types of signs including hand signals.

(3) Such training referred to in paragraph (1) and (2) became subject to the necessary updating where this is required by changes in the activities on board.

Art.14. - Without prejudice to the provisions of the Government Decision no. 1007/2006 regarding of minimal provisions referred to safety and health relative to the medical assistance on vessels board, any person likely to command a vessel shall be given detailed training on:

- a) the prevention of occupational illness and labour accidents on board and the steps to be taken in event of accident;
- b) stability and maintenance of the vessel under all foreseeable conditions of loading and during the fishing operations;
- c) navigation and radio communication, including procedures.

Art.15. - The consultation of workers and/or their representatives and their participation in discussions on the matters covered by the present Government Decision take place in accordance with the provisions of the Law no. 319/2006.

CHAPTER V **Final provisions**

Art.16. - Purely technical adaptations of the annexes take account of:

- a) the adoption of regulations in the matter of technical harmonization and standardization concerning certain aspects of safety and health on board vessels, and/or
- b) technical progress, evolution of international regulations or specifications and knowledges in the field of safety and health on board vessels.

Art.17. – Annexes no.1 to 4 are integrant parts of the present decision.

Art.18. – The present Government Decision enters into force on 1st of October 2006.

Art.19. – The Ministry of Labor, Social Solidarity and Family will report every four years to the European Commission on the implementation of the present decision, indicating the view points of the social partners.

Art.20. – The present decision transposes the provisions of the European Directive no. 93/103/EEC of 23rd of November 1993 regarding the minimum safety and health requirements applicable to work on board fishing vessels, published in the Official Journal of European Communities (OJCE) no. L 307 of 13th of December 1993.

PRIME – MINISTER

CĂLIN POPESCU – TĂRICEANU

ANNEX NO.1

MINIMUM SAFETY AND HEALTH REQUIREMENTS FOR NEW FISHING VESSELS

Preliminary note

The obligations laid down in the present annex apply whenever required by the features of the workplace, the activity, the circumstances or a risk on board a new fishing vessel.

1. Seaworthiness and stability

1.1. The vessel must be maintained in a good seaworthy condition and be properly equipped appropriate to its purpose and use.

1.2. Information on the vessel's characteristics of stability must be available on board and must be accessible to the men on watch.

1.3. All vessels must be sufficiently stable when intact in the conditions of service for which they are intended.

The skipper must take the precautionary measures necessary to maintain adequate stability of the vessel.

Instructions supplied concerning the vessel's stability must be strictly observed.

2. Mechanical and electrical installations

2.1. Electrical installations must be designed and constructed as well as not to present any danger and as well as to ensure:

a)- protection for the crew and vessel from electrical hazards,

b)- the proper functioning of all equipment necessary to maintain the vessel in normal operational and living conditions without recourse to an emergency power supply,

c)- the operation of electrical equipment essential for safety in all emergencies.

2.2. An emergency electrical power source must be provided.

Except in open vessels, it must be located outside the engine room and must, in all cases, be so arranged as to ensure in the event of fire or other failure of the main electrical installation, simultaneous functioning for at least three hours of:

a)- the internal communication system, fire detectors and emergency signals,

b)- the navigation lights and emergency lighting,

c)- the radio communication system,

d)- the emergency electrical fire pump where present.

2.3 If the emergency electrical power source is an accumulator battery and the main electrical power source fails, the accumulator battery must be automatically connected to the emergency electrical switchboard and supply power for an uninterrupted period of three hours to the systems referred to in the first, second and third indents of the second paragraph.

2.4 The main electrical switchboard and the emergency switchboard must, to the extent possible, be installed in such a way that they cannot be exposed simultaneously to water or fire.

2.5. Switchboards should be clearly marked; fuse boxes and fuse holders should be checked at regular intervals to ensure that the correct rating of fuse is being used.

2.6. Compartments housing electrical storage batteries must be adequately ventilated.

2.7. The electronic aids to navigation should be tested frequently and well maintained.

2.8. All equipment used in hoisting and all characteristics equipment should be tested and examined at regular intervals.

2.9. All parts of hauling gear, hoisting gear and related equipment should be maintained in good repair and working order.

2.10. Where refrigeration plants and compressed air systems are installed they should be well maintained and examined at regular intervals.

2.11. Cooking and domestic appliances using heavy gases should be used only in well ventilated spaces and care should be taken to avoid any dangerous accumulation of gas.

2.12. Cylinders containing flammable and other dangerous gases should be clearly marked as to their contents and stowed on open decks.

2.13. All valves, pressure regulators and pipes leading from the cylinders should be protected against damage.

3. Radio communications installation

The radio communications installation must permit contact at all times with at least one coastal or land-based station, taking into account the normal conditions for propagation of radio waves.

4. Emergency routes and exits

4.1. Routes and exits which can be used as emergency routes and exits must be unobstructed and easily accessible at all times and lead out as directly as possible to the open deck or to a safe area and thence to the survival craft, so that workers can evacuate their workstations or living areas quickly and as safely as possible.

4.2. The number, distribution and dimensions of the routes and exits which can be used as emergency routes and exits must depend on the use, equipment and dimensions of workplaces and living areas and on the maximum potential number of persons present.

Exits which can be used as emergency exits and which are closed must be immediately and readily operable in an emergency by any worker or by rescue teams.

4.3. Emergency doors and other emergency exits must be adequately weatherproof and watertight for their location and particular function.

4.4. Emergency doors and other emergency exits must be as fire-resistant as the bulkheads.

4.5. Emergency routes and exits must be indicated by signs in accordance with national provisions of Government Decision no. 971/2006, regarding of minimal requirements for the provision of safety signing and/or healthy signing at workplace.

Such signs must be placed at appropriate points and be made to last.

4.5. Escape routes and facilities and emergency exits requiring illumination must be provided with emergency lighting of adequate intensity in case the lighting fails.

5. Fire detection and fire fighting

5.1. Depending on the dimensions and use of the vessel, the equipment it contains, the physical and chemical properties of the substances present and the maximum potential

number of persons present, living quarters and enclosed workplaces, including the engine-room and the fish hold if necessary, must be equipped with appropriate fire-fighting equipment and, as necessary, with fire detectors and alarm systems.

5.2. Fire-fighting equipment must always be kept in its proper location, maintained in good working order, and be available for immediate use.

5.3. Workers must be familiar with the locations of fire-fighting equipment, the way it works and how it should be used.

5.4. The presence of extinguishers and other portable fire-fighting equipment must always be checked before the vessel gets under way.

5.5. Manually-operated fire-fighting equipment must be easily accessible and simple to use and must be indicated by signs in accordance with provisions of Government Decision no. 971/2006 concerning the safety and/or health signs at workplace.

Such signs must be placed at appropriate points and be made to last.

5.6. Fire-detection and alarm systems should be regularly tested and well maintained.

5.7. Fire-fighting drills shall be carried out periodically.

6. Ventilation of enclosed workplaces

6.1. Steps must be taken to see that there is sufficient fresh air in enclosed workplaces, having regard to the working methods used and the physical conditions demands placed on the workers.

6.2. If a mechanical ventilation system is used, it must be maintained in good condition of functioning.

7. Temperature of working areas

7.1. The temperature in working areas must be adequate for the human body during the hours of working, having regard to the work methods used, the physical demands placed on the workers and the actual or potential weather conditions in the area in which the vessel operates.

7.2. The temperature in living quarters, sanitary facilities, canteens and first-aid rooms must, where those areas exist, be appropriate to the particular purpose of such areas.

8. Natural and artificial lighting of workplaces

8.1. Workplaces must as far as possible receive sufficient natural light and be equipped with artificial lighting suitable for the fishing operations in hand, without placing workers' safety and health in danger or jeopardizing other vessels.

8.2. Installations for the lighting of working areas, stairs, ladders and passageways must be placed in such a way that the type of lighting provided poses no risk of accident to workers and no hindrance to the navigation of the vessel.

8.3. Workplaces in which workers are especially exposed to risks in the event of failure of artificial lighting must be provided with emergency lighting of adequate intensity.

8.4. Emergency lighting must be maintained in an efficient operating condition and be tested at regular intervals.

9. Decks, bulkheads and deckheads

9.1. Spaces accessible to workers must be not slippery but must be anti-slip or be provided with must be non-slip or anti-slip or be provided with devices to prevent falls and kept free of obstacles as far as possible.

9.2. Workplaces containing workstations must be adequately soundproofed and insulated, bearing in mind the type of tasks involved and the physical activity of workers.

9.3. The surface of decks, bulkheads and deckheads in working areas must be such that they can be cleaned or refurbished to an appropriate standard of hygiene.

10. Doors

10.1. Means should be provided so that the doors can be at all times operated from the inside without special equipment.

The doors must be operable from either side when workplaces are in use.

10.2. Doors, and in particular sliding doors, where such have to be used, must function as safely as possible for the workers, especially in adverse weather and sea conditions.

11. Traffic routes - danger areas

11.1. Passageways, trunks, the outer part of deckhouses and all traffic routes in general must be equipped with guard rails, grab rails, lifelines and winch hanging or other means of ensuring the safety of workers in the course of activities on board.

11.2. If there is a risk that workers may fall through openings in the deck, or from one deck to another, adequate protection should be provided wherever possible.

Where guard rails provide such protection, they must be at least one meter high.

11.3. Access to installations above the deck for operations or maintenance purposes must be such as to ensure workers' safety.

Guard rails or similar protective devices of appropriate height must be provided to prevent falls.

11.4. Bulwarks or other means provided to prevent persons falling overboard must be maintained in an efficient condition.

Bulwarks must be fitted with freeing ports or other similar devices to enable water to drain away quickly.

11.5. On stern fishing vessels with ramps, the upper part of the ramp must be fitted with a gate or other means of securing it of the same height as the bulwarks or other adjacent means, to protect workers from the risks of falling into the ramp.

This gate or other device must be easily opened and closed, preferably by remote control, and must be open only for casting the net or for haul it in.

12. Layout of workstations

12.1. Working areas must be kept clear and, as far as possible, be protected from the sea and provide adequate protection for workers against falling on the vessel or falling overboard.

Handling areas must be sufficiently spacious, in terms of both height and surface area.

12.2. If the engines are controlled from the engine room, they must be controlled from a separate area, soundproofed and insulated from the engine room per se and accessible without getting over the latter.

The navigating bridge is considered to be an area that meets the requirements of the first subparagraph.

12.3. The controls for the hauling gear must be installed in an area sufficiently large to enable operators to work unhindered.

Likewise, the hauling gear must also have appropriate safety devices for emergencies, including emergency stop facilities.

12.4. The hauling gear operator must have an adequate view of the hauling gear and the workers at work.

If the hauling gears are controlled from the bridge, the operator should also have a clear view of the workers at work, either directly or via any other suitable medium.

12.5. A reliable communications system must be used between the bridge and the working deck.

12.6. A sharp look out should always be maintained and the crew warned of the imminent danger of heavy oncoming seas during fishing operations or when other work is being done on deck.

12.7. Contact with bare ropes and warps and with moving parts of the equipment must be minimized by installing protective devices.

12.8. Controls must be installed for moving masses, particularly on trawlers: devices to immobilize the otter boards,

b) devices to control the swinging motion of the fishing net bottom.

13. Living quarters

13.1. The location, structure, soundproofing, means of insulation and layout of the workers' living quarters and facilities, where these exist, and means of access thereto should be such as to provide adequate protection against weather and sea, vibration, noise and unpleasant odors from other parts of the vessel likely to disturb the workers during their period of rest.

13.2. Where the design, dimensions and/or purpose of the vessel allow, the workers' living quarters must be located so as to minimize the effects of motion and acceleration.

13.3. Appropriate measures should be taken as far as possible to protect non-smokers from discomfort caused by tobacco smoke.

13.4. The workers' living quarters should be properly ventilated to ensure a constant supply of fresh air and prevent condensation.

Appropriate lighting must be provided in the living quarters, with:

a) adequate normal general lighting,

b) reduced general lighting to avoid disturbing workers who are resting, and

c) local lighting in each berth or living quarters.

13.5. The galley and mess, where these exist, should be of adequate size, well lit and ventilated and easy to clean.

Refrigerators or other low-temperature food-storage equipment must be provided.

14. Sanitary facilities

14.1. On vessels with living quarters, shower facilities with hot and cold running water, washbasins and toilets must be properly equipped and installed and the respective areas must be properly ventilated.

14.2. Every worker must have the use of a place where he can keep his clothes.

15. First aid

On all vessels first-aid equipment must be available in accordance with the provisions of the national legislation that transpose the Annex II provisions of Directive no. 92/29/EEC, regarding of minimal requirements of safety and health for improving of medical assistance on vessels board.

16. Accommodation ladders and gangways

An accommodation ladder, gangway or other similar equipment providing an appropriate, safe means of boarding the vessel must be available.

17. Noise

All appropriate technical measures must be taken to reduce the noise level at workplaces and in the living quarters as far as possible, taking into consideration the size of the vessel.

ANNEX No.2

MINIMUM SAFETY AND HEALTH REQUIREMENTS FOR EXISTING FISHING VESSELS

Preliminary note

The obligations laid down in the present annex apply, in so far as the structural characteristics of the existing fishing vessel permit, whenever required by the features of the workplace, the activity, the circumstances or a risk on board an existing fishing vessel.

1. Seaworthiness and stability

- 1.1. The vessel must be maintained in a seaworthy condition and be properly equipped appropriate to its purpose and use.
- 1.2. Where it exists, information on the vessel's stability must be available on board and must be accessible to the men on watch.
- 1.3. All vessels must be sufficiently stable when intact in the conditions of service for which they are intended.
- 1.4. The skipper must take the necessary precautionary measures in order to maintain adequate stability of the vessel.
- 1.5. Instructions supplied concerning the vessel's stability must be strictly observed.

2. Mechanical and electrical installations

- 2.1. Electrical installations must be designed and constructed so as not to present any danger and so as to ensure:
 - a) protection for the crew and vessel from electrical risks,
 - b) the proper functioning of all equipment necessary to maintain the vessel in normal operational and living conditions without recourse to an emergency power supply,
 - c) the operation of electrical equipment essential for safety in all emergencies.
- 2.2. An emergency electrical power source must be provided.

Except in open vessels, the emergency electrical power source must be located outside the engine room and in all cases be so arranged as to ensure, in the event of fire or other failure of the main electrical installation, simultaneous functioning for at least three hours of:

 - a) the internal communication system, fire detectors and emergency signals,
 - b) the navigation lights and emergency lighting,
 - c) the radio installation,
 - d) the emergency electrical fire pump where present.
- 2.3. If the emergency electrical power source is an accumulator battery and the main electrical power source fails, the accumulator battery must be automatically connected to the emergency electrical switchboard and supply power for an uninterrupted period of three hours to the systems referred to in the subparagraph a, b and c of 2.2. paragraph.
- 2.4. The main electrical switchboard and the emergency switchboard must, to the extent possible, be installed in such a way that they cannot be exposed simultaneously to water or fire.
- 2.5. Switchboards must be clearly marked; fuse boxes and fuse holders should be checked at regular intervals to ensure that the correct rating of fuse is being used.
- 2.6. Compartments housing electrical storage batteries must be adequately ventilated.
- 2.7. Electronic aids to navigation should be tested frequently and well maintained.
- 2.8. All equipment used in hoisting should be tested and examined at regular intervals.
- 2.9. All parts of hauling gear, hoisting gear and related equipment should be maintained in good repair and working order.
- 2.10. Where refrigeration plants and compressed air systems are installed, they should be well maintained and examined at regular intervals.
- 2.11. Cooking and domestic appliances using heavy gases should be used only in well-ventilated spaces and care should be taken to avoid any dangerous accumulation of gas.
- 2.12. Cylinders containing flammable and other dangerous gases should be clearly marked as to their contents and stowed on open decks.
- 2.13. All valves, pressure regulators and pipes leading from the cylinders should be protected against damage.

3. Radio installation

The radio installation must permit contact at all times with at least one coastal or land-based station, taking into account the normal conditions for propagation of radio waves.

4. Emergency routes and exits

4.1. Routes and exits which can be used as emergency routes and exits must be unobstructed and easily accessible at all times and lead out as directly as possible to the open deck or to a safe area and thence to the survival craft so that workers can evacuate their workstations or living areas quickly and as safely as possible.

4.2. The number, distribution and dimensions of the routes and exits which can be used as emergency routes and exits must depend on the use, equipment and dimensions of workplaces and living areas and on the maximum potential number of persons present.

4.3. Exits which can be used as emergency exits and which are closed must be immediately and readily operable in an emergency by any worker or by rescue teams.

4.4. Emergency routes and exits must be indicated by signs in accordance with Government Decision no. 971/2006 regarding of minimum requirements for the provision of safety signing and/or healthy signing at work. Such signs must be placed at appropriate points and be made to last.

4.5. Escape routes and facilities and emergency exits requiring illumination must be provided with emergency lighting of adequate intensity in case the lighting fails.

5. Fire detection and fire fighting

5.1. Depending on the dimensions and use of the vessel, the equipment it contains, the physical and chemical properties of the substances present and the maximum potential number of persons present, living quarters and enclosed workplaces, including the engine-room and the fish hold if necessary, must be equipped with appropriate fire-fighting equipment and, as necessary, with fire detectors and alarm systems.

5.2. Fire-fighting equipment must always be kept in its proper location, maintained in good working order, and be available for immediate use.

5.3. The workers must be familiar with the location of fire-fighting equipment, the way it works and how it should be used.

5.4. The presence of extinguishers and other portable fire-fighting equipment must always be checked before the vessel gets under way.

5.5. Manually operated fire-fighting equipment must be easily accessible and simple to use and must be indicated by signs in accordance with the provisions of the Government Decision no. 971/2006.

Such signs must be placed at appropriate points and be made to last.

5.6. Fire-detection and alarm systems should be regularly tested and well maintained.

5.7. Fire-fighting drills shall be carried out at regular intervals.

6. Ventilation of enclosed workplaces

6.1. Steps must be taken to see that there is sufficient fresh air in enclosed workplaces, having regard to the working methods used and the physical demands placed on the workers.

6.2. If a mechanical ventilation system is used, it must be maintained in good condition.

7. Temperature of working areas

7.1. The temperature in working areas must be adequate for the human body during the hours of working, having regard to the work methods used, the physical demands placed on the workers and the actual or potential weather conditions in the area in which the vessel operates.

7.2. The temperature in living quarters, sanitary facilities, canteens and first-aid rooms must, where those areas exist, be appropriate to the particular purpose of such areas.

8. Natural and artificial lighting of workplaces

8.1. Workplaces must as far as possible receive sufficient natural light and be equipped with artificial lighting suitable for the operations in hand, without placing workers' safety and health in danger or jeopardizing the navigation of other vessels.

8.2. Lighting installations in working areas, stairs, ladders and passageways must be placed in such a way that the type of lighting envisaged poses no risk of accident to workers and no hindrance to the navigation of the vessel.

8.3. Workplaces in which workers are especially exposed to risks in the event of failure of artificial lighting must be provided with emergency lighting of adequate intensity.

8.4. Emergency lighting must be maintained in an efficient operating condition and be tested at regular intervals.

9. Decks, bulkheads and deckheads

9.1. Spaces accessible to workers must be non-slip or anti-slip or be provided with devices to prevent falls and kept free of obstacles as far as possible.

9.2. Workplaces containing workstations must, in so far as possible, be adequately soundproofed and insulated, bearing in mind the type of tasks involved and the physical activity of workers.

9.3. The surface of decks, bulkheads and deckheads in working areas must be such that they can be cleaned or refurbished to an appropriate standard of hygiene.

10. Doors

10.1. Means should be provided so that doors can at all times be operated from the inside without special equipment.

The doors must be operable from either side when workplaces are in use.

10.2. Doors and in particular sliding doors, where such have to be used, must function as safely as possible for the workers, especially in adverse weather and sea conditions.

11. Traffic routes - danger zones

11.1. Passageways, trunks, the outer part of deckhouses and all traffic routes in general must be equipped with guardrails, grab rails and lifelines or other means of ensuring the safety of workers in the course of activities on board.

11.2. If there is a risk that workers may fall through openings in the deck, or from one deck to another, adequate protection should be provided wherever possible.

11.3. Access to installations above the deck for operation or maintenance purposes must be such as to ensure workers' safety.

Guard rails or similar protective devices of appropriate height must be provided to prevent falls.

11.4. Bulwarks or other means provided to prevent persons falling overboard must be maintained in an efficient condition.

Bulwarks must be fitted with freeing ports or other similar devices to enable water to drain away quickly.

11.5. On stern trawlers with ramps, the ramp must be fitted with a gate or other means of securing it of the same height as the bulwarks or other adjacent means, to protect workers from the risk of falling into the ramp.

This gate or other device must be easily opened and closed and must be open only for casting the net or for hauling it in.

12. Layout of workstations

12.1. Working areas must be kept clear and, as far as possible, be protected from the sea and provide adequate protection for workers against falling on the vessel or falling overboard.

Handling areas must be sufficiently spacious, in terms of both height and surface area.

12.2. If the engines are controlled from the engine room, they must be controlled from a separate area, soundproofed and insulated from the engine room per se and accessible without passing through the latter.

The navigating bridge is considered to be an area that meets the requirements of the first subparagraph.

12.3. The controls for the hauling gear must be installed in an area sufficiently large to enable operators to work unhindered.

The hauling gear must also have appropriate safety devices for emergencies, including emergency stop facilities.

12.4. The hauling gear operator must have an adequate view of the hauling gear and the workers at work.

If the hauling gear is controlled from the bridge, the operator should also have a clear view of the workers at work, either directly or via any other suitable medium.

12.5. A reliable communications system must be used between the bridge and the working deck.

12.6. A sharp look out should always be maintained and the crew warned of the imminent danger of heavy oncoming seas during fishing operations or when other work is being done on deck.

12.7. Contact with bare ropes and warps and with moving parts of the equipment must be minimized by installing protective devices.

12.8. Controls must be installed for moving masses, particularly on trawlers:

a) devices to immobilize the otter boards,

b) devices to control the swinging motion of the fishing net bottom.

13. Living quarters

13.1. The workers' living quarters, where they exist, must be such as to minimize noise, vibration, the effects of motion and acceleration, and unpleasant odors from other parts of the vessel.

Appropriate lighting must be installed in the living quarters.

13.2. The galley and mess, where they exist, should be of adequate size, adequately lit and ventilated and easy to clean.

Refrigerators or other low-temperature food-storage equipment must be provided.

14. Sanitary facilities

On vessels with living quarters, toilets, washbasins and, if possible, a shower must be installed and the respective areas must be properly ventilated.

15. First aid

On all vessels first-aid equipment must be available in accordance with the provisions of Government Decision no. 1007/2006 regarding of the minimum requirements of safety and health concerning of medical assistance on vessels board.

16. Accommodation ladders and gangways

An accommodation ladder, gangway or other similar equipment providing an appropriate, safe means of boarding the vessel must be available.

ANNEX No.3

MINIMUM SAFETY AND HEALTH REQUIREMENTS FOR CONCERNING LIFE-SAVING AND SURVIVAL EQUIPMENT

Preliminary note

The obligations laid down in this Annex apply wherever required by the features of the workplace, the activity, the circumstances or a risk on board a vessel.

1. Vessels must carry adequate life-saving and survival equipment, including adequate means of recovering workers from the water, and radio rescue, in particular an emergency position-indicating radio beacon with a hydrostatic release mechanism, taking account of the number of persons on board and the area in which the vessel is operating.
2. All items of life-saving and survival equipment must be kept in their proper locations, maintained in good working order and be available for immediate use.
The workers before the vessel leaves port and during the voyage must check them.
3. The life-saving and survival equipment must be inspected at regular intervals.
4. All workers must receive proper training and appropriate instructions in anticipation of an emergency.
5. If the length of the vessel exceeds 45 meters or if five or more workers are carried, a muster list must be provided with clear instructions for each worker, which must be followed in case of emergency.
6. Musters of workers for survival drill should be carried out each month in port and/or at sea.
These drills must ensure that the workers thoroughly understand and are exercised in the duties that they have to perform with respect to the handling and operation of all life-saving and survival equipment.
7. Workers must be trained in the setting up and operation of the portable radio equipment, where carried.

ANNEX No.4

MINIMUM SAFETY AND HEALTH REQUIREMENTS CONCERNING PERSONAL PROTECTIVE EQUIPMENT

Preliminary note

The obligations laid down in this Annex apply whenever required by the features of the workplace, the activity, the circumstances or a risk on board a vessel.

1. Where risks to the safety and health of workers cannot be prevented or sufficiently limited by collective or technical means of protection, they must be provided with personal protective equipment.
2. Personal protective equipment in the form of clothing or worn over clothing must be in bright colors, contrasting with the marine environment and clearly visible.